TexChem

DOT

Nity DOT® odporne na zużycie

Typ 93

DOT® odporne na zużycie – nity te służą do pewnego i trwałego mocowania. Sprawdziły się jako najlepszy rodzaj mocowania dla potrzeb technicznych i przemysłowych. Doświadczenie pokazało, że montaż nitów to proces bezproblemowy, tworzący wytrzymałe konstrukcje, które przez lata nie straciły swojego kształtu. Dzięki zamontowanej na środku nitu sprężynie (gniazdo) mogą być stosowane wszędzie, zapewniając bezpieczne mocowanie.

Dzięki unikalnemu procesowi powlekania kółek DOT uchwyt wnika w każdą, nawet nierówną powierzchnię materiału bez konieczności przebijania otworów.

Różna wysokość uchwytów pozwala na zastosowanie ich do materiałów o różnych grubości. Spełnia wymagania norm rządowych USA MIL-10884 i MS27980 Styl 2.

DOT® Durable Snap Fasteners

Division 93

DOT® Durable is the dot snap fastener to use when superior snap action and holding strength are required. With a reputation of being the best performing snap fasteners of their type for industrial applications, DOT Durable snap fasteners' heavy-duty construction assures a firm grip that will remain secure through years of use. DOT Durable sockets are constructed to narrow tolerances that ensure consistent snap action snap after snap. The design of the socket including its floating ring is superior to other socket types in performing on heavy-duty applications.

A unique process in the fabrication of the DOT eyelets/posts ensures that DOT Durable snap fasteners penetrate even the most rugged materials without the need for a pre-punched hole. Various eyelet/post lengths ensure adaptability to a wide range of material thicknesses, and because it is self-piercing, no pre-punching is needed. Available in a variety of eyelet/post lengths and in a variety of Caps, Sockets, Studs, and Screw Studs. Conforms to US Government MIL-10884 specifications, MS27980 Style 2.

CAPS	SOCKETS	STUDS	POSTS
93-10112 D: .600/15.24mm H: .318/8.07mm X2	**93-10224** Normal Action XB, X5	**93-10370** Standard BS, SS, NS	**93-10412** D: .555/14.10mm H: .240/6.10mm BS, SS, NS
93-10127 D: .600/15.24mm H: .240/6.10mm X2, XS, XN, X8	**93-10224** Hard Action XX, X6, XN	**93-10373** Flangeless BS, NS	**93-10413** D: .555/14.10mm H: .295/7.49mm BS, SS, NS
93-10128 D:600/15.24mm H:170/4.32mm X2, XS, XN, X8	**93-10231** Easy Action XB	**93-10379** Deep Shelf BS, SS	**93-10414** D: .555/14.10mm H: .370/9.40mm BS
93-10129 D: .525/13.33mm H: .195/4.95mm X2	**93-10616** Socket Buckle XN	**93-10342** Gypsy Stud XB	
93-10150 **Mariner™** D: .600/15.24mm H: .187/4.76mm XV			



WINDSHIELD CLIP STUDS

93-10388
3/4″
XX

93-10391
7/8″
XX

VELTEX™ CARPET SNAPS

93-10223
BS

93-10222
XB

BLIND RIVET STUDS

93-10314
H: .299/7.59mm
X8

93-10319
H: .486/12.34mm
X8



PLASTICS

CAPS

93-10419
D: .555/14.10mm
H: .310/7.87mm
PC

SOCKETS

93-10233
PC

STUDS

93-10380
PC

POSTS

93-10419
D: .555/14.10mm
H: .310/7.87mm
PC

SCREW STUDS

93-10301
X8, b

93-10302
X8, c

93-10362
*XX, a

93-10393
XB, X8, XN, a, h

93-10934
X8, j

93-10704
X8, XN, d

93-10708
XB, *XX, e

93-10725
*XX, X8, g

CAPS	SOCKETS	STUDS	POSTS
94-12105 D: .454/11.53mm H: .140/3.55mm XB	**94-12205** Normal Action XB, X5	**94-12302** Narrow Flange BS, SS	**94-12402** D: .495/12.57mm H: .195/4.95mm BS
94-12108 D: .525/13.34mm H: .126/3.20mm X2, XS	**94-12206** Hard Action XX	**94-12303** Wide Flange BS, SS	**94-12404** D: .500/12.70mm H: .245/6.22mm BS
94-12126 D: .525/13.34mm H: .185/4.70mm X2			**94-12405** D: .425/10.80mm H: .245/6.22mm BS, SS
			94-12407 D: .425/10.80mm H: .195/4.95mm BS, SS



Nity jednostronne Lift-the-DOT®

Typ 90

Mocne nity, które po zablokowaniu można zerwać tylko z jednej, czwartej strony. Stąd pochodzi nazwa handlowa Lift-the-DOT – nitowane klipsy. Nity odporne na korozję są wykonane z miedzi lub innych metali nieżelaznych, dzięki czemu są łatwe w użyciu w bardzo trudnych warunkach (np. kabura na broń).

Dostępne w różnych długościach, grubościach i materiałach. Lift-the-DOT spełnia rządowe normy wojskowe MIL-10884 i MS27977 Styl 1.

Lift-the-DOT® Lift-the-DOT® Directional Snap Fasteners

Division 90

Strong and heavy-duty, Lift-the-DOT® fasteners lock on three sides and are opened by lifting the fourth side where DOT and Lift-the-DOT trademarks appear. Rust-resistant, Lift-the-DOT fasteners are constructed of all brass or other non-ferrous metals ensuring that they can be used in the most difficult environments such as gun holsters.

Available in a variety of post lengths, sockets and studs to accommodate a wide range of material thicknesses, Lift-the-DOT conforms to US Government MIL-10884 specifications, MS27977 Style 1.

SOCKETS	BACK PLATES	POSTS	WASHERS
90-16205 H: .205/5.21mm XX	**90-16506** BS	**90-16349** BS	**90-16501** BS
90-16206 H: .275/6.99mm XX	**90-16510** Flexwasher PS	**90-16358** XB	**90-16509** BS
		90-16347 XB	

WINDSHIELD CLIPS	SCREW STUDS		
90-16376 3/4" XX	**90-16317** XB, h	**90-16362** XB, *XX, d	**90-16360** X8, a
90-16377 7/8" XX		**90-16366** *XX, a	

Nity obrotowe Common Sense®

Typ 91

Te nity nigdy nie otworzą się przypadkowo. Każdy nit zawiera mechanizm sprężynowy, który utrzymuje go pod ciśnieniem w żądanej pozycji i ręcznie powraca do pozycji głównej. Dzięki temu nadają się one zarówno do powierzchni miękkich, jak i twardych.

Common Sense® Turn Button Fasteners

Division 91

These positive locking fasteners will never open accidentally. Each fastener is assembled with a spring mechanism that holds the fastener under tension in the desired position until turned and released by hand. Demonstrating dependable performance in even the most difficult environments, Common Sense is available in a variety of turn button styles that can be used on both hard and soft surface applications.

TURN BUTTONS		WASHERS	GROMMETS
91-78322 H: .683/17.35mm XB	**91-78315** H: .790/20.06mm *XX	**91-78505** BS	**91-78403** H: .335/8.51mm BS
91-78323 H: .790/20.06mm XB	**91-78324** H: .790/20.06mm XB, X8, f	**91-78510** BS	**91-78404** H: .385/9.78mm BS
	91-78325 H: .860/21.84mm XB, f	**91-78511** Flexwasher PS	



TURN BUTTONS		BACK PLATES
91-78317 H: .790/20.06mm XB	**91-78318** H: .860/21.84mm XB	**91-78502** BS
91-78332 H: .700/17.78mm XB	**91-78333** H: .838/21.28mm XB	**91-78507** BS

PULL-the-DOT®

Typ 92

Te wytrzymałe, trójskładnikowe nity są odpinane tylko wtedy, gdy przyłożona jest określona siła. Pull-the-DOT mogą być stosowane zarówno do nitów w celu normalnego użytku, jak i do użytku w obiektach narażonych na ekstremalne warunki atmosferyczne.

PULL-the-DOT®

Division 92

This heavy-duty three-sided fastener withstands extreme pressure without unlocking. Self-piercingon standard application materials, Pull-the-DOT has a well-earned reputation for performing in harshenvironments.

CAPS	SOCKETS	STUDS	POSTS
92-18100 D:598/15.19mm H:166/4.22mm XE	**92-18201** Normal Action XB	**92-18303** BS	**93-10412** D:555/14.10mm H:240/6.10mm BS
92-18103 D: 598/15.19mm H:236/5.99mm XE	**92-18201** Hard Action XX	**92-18307** Screw Stud XB, a	**93-10413** D:555/14.10mm H:295/7.49mm BS

BASE MATERIALS	SCREW TYPES
BS – All Brass X2 – All Brass XB – All Brass XE – All Brass SS – All Steel X6 – All Steel/Other NS – All Stainless Steel XN – All Stainless Steel PC – All Plastic PS – All Plastic X5 – Brass/Steel X8 – Brass/Stainless XV – Brass/Plastic XX – Brass/Other	a - #8-15 Self-Tapping b - #8-18 Self-Drilling c - #10-16 Self-Drilling d - #8-32 Machine e - #10-32 Machine f - #7 Wood Screw g - #8-18 Self-Tapping h - #8 Wood Screw i - #12-14 Self-Tapping j - #10-16 Self-Tapping

Notatki / Notes

TexChem Sp. z o.o.

+48 664 785 955
+48 698 849 922
biuro@texchem.info.pl
www.texchem.info.pl
ul. Gościnna,11, Blizne Łaszczyńskiego, 05-082 Stare Babice, Polska